

## SERIE RXB

### RXB-606

6 X 600 X 400 mm.

6 x GN 1/1



9.100 W



250° C



90 Kg.



400 V - 50/60 Hz



#### CARACTERÍSTICAS features

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>● DIMENSIONES INTERNAS: (W)490x(D)655x(H)630 mm<br/><i>cooking chamber dimension</i></li> </ul> | <ul style="list-style-type: none"> <li>● POTENCIA: 9.100 W<br/><i>power</i></li> </ul>                    |
| <ul style="list-style-type: none"> <li>● DIMENSIONES EXTERNAS: (W)755x(D)890x(H)840 mm<br/><i>external dimension</i></li> </ul>        | <ul style="list-style-type: none"> <li>● TEMPERATURA MÁXIMA: 250° C<br/><i>max temperature</i></li> </ul> |
| <ul style="list-style-type: none"> <li>● DISTANCIA ENTRE PARRILLAS: 80 mm.<br/><i>distance between trays</i></li> </ul>                | <ul style="list-style-type: none"> <li>● PESO: 90 Kg.<br/><i>weight</i></li> </ul>                        |
| <ul style="list-style-type: none"> <li>● CONEXIÓN: Trifásica 3F+N+T<br/><i>3p + n + e three phase</i></li> </ul>                       | <ul style="list-style-type: none"> <li>● VOLTAJE: 400 V / 50-60 Hz<br/><i>Voltage</i></li> </ul>          |

#### EQUIPAMIENTO equipment

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>● Temporizador 0-120 min. + modo continuo<br/><i>timer 0-120 min. + continuous function.</i></li> <li>● Alarma fin de ciclo <i>Cycle end alarm</i></li> <li>● Micro de puerta <i>Door safety switch</i></li> <li>● Termostato de seguridad <i>Safety thermostat</i></li> </ul> | <ul style="list-style-type: none"> <li>● Lámpara interior <i>Halogen chamber light</i></li> <li>● Inversor de giro <i>Reversing gear</i></li> <li>● Conexión agua ¾ <i>Water connection ¾</i></li> <li>● Humedad regulable 0-100% <i>Adjustable humidity 0% - 100 %</i></li> <li>● Vidrio abatible para limpieza <i>Folding inner glass for cleaning</i></li> </ul> |
|---|---|

#### OPCIONES (PVP) options (rrp)

- CAMBIO APERTURA PUERTA: 380 €  
*change opening door*

PVP rrp RXB-606