



3.100 W



250° C



34 Kg.



230 V / 50Hz



CARACTERÍSTICAS features

- | | |
|------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> ● DIMENSIONES INTERNAS: (W)450x(D)340x(H)345 mm
<i>cooking chamber dimension</i> | <ul style="list-style-type: none"> ● POTENCIA: 3100 W
<i>power</i> |
| <ul style="list-style-type: none"> ● DIMENSIONES EXTERNAS: (W)590x(D)675x(H)540 mm
<i>external dimension</i> | <ul style="list-style-type: none"> ● TEMPERATURA MÁXIMA: 250° C
<i>max temperature</i> |
| <ul style="list-style-type: none"> ● DISTANCIA ENTRE PARRILLAS: 80 mm.
<i>distance between trays</i> | <ul style="list-style-type: none"> ● PESO: 34 Kg.
<i>weight</i> |
| <ul style="list-style-type: none"> ● CONEXIÓN: SCHUKO_MONOFASICO <i>single phase connection</i> | <ul style="list-style-type: none"> ● VOLTAJE: 230 V - 50 Hz.
<i>Voltage</i> |
| <ul style="list-style-type: none"> ● DOTACIÓN: 4 Bandejas aluminio perforadas
<i>including: 4 perforated aluminium tray</i> | |

EQUIPAMIENTO equipment

- Temporizador 0-60 min. + modo continuo *timer 0-60 min. + continuous function.*
- Apertura reversible modelo (puerta lateral) *Reversible opening door (side door model) (RXL)*
- Termostato seguridad *Safety thermostat*

OPCIONES (PVP) options (rrp)

- | | | |
|----------------|------------------------------------|--------------|
| ● GRILL 1,4 kW | ● HUMIFICADOR
<i>humidifier</i> | ● KIT GN 2/3 |
|----------------|------------------------------------|--------------|

PVP rrp **RX-304**

PVP rrp **RXL-304**