



5.700 W




250° C



42 Kg



400/230 V / 50-60 Hz



## CARACTERÍSTICAS features

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>● DIMENSIONES INTERNAS: (W)620x(D)450(H)350 mm<br/><i>cooking chamber dimension</i></li> <li>● DIMENSIONES EXTERNAS: (W)760x(D)800x(H)545 mm<br/><i>external dimension</i></li> <li>● DISTANCIA ENTRE PARRILLAS: 80 mm.<br/><i>distance between trays</i></li> <li>● CONEXIÓN: Trifásica 3F+N+T / Monofásica 3p + n + e<br/><i>three phase / single phase</i></li> <li>● DOTACIÓN: 4 Parrillas<br/><i>including: 4 wire rack</i></li> </ul> | <ul style="list-style-type: none"> <li>● POTENCIA: 5.700 W<br/><i>power</i></li> <li>● TEMPERATURA MÁXIMA: 250° C<br/><i>max temperature</i></li> <li>● PESO: 39 Kg.<br/><i>weight</i></li> <li>● VOLTAJE: 230 V - 50/60 Hz.<br/><i>Voltage</i></li> </ul> |
|--|--|

## EQUIPAMIENTO equipment

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>● Temporizador 0-60 min. + modo continuo<br/><i>timer 0-60 min. + continuous function.</i></li> <li>● Alarma fin de ciclo <i>Cycle end alarm</i></li> <li>● Micro de puerta <i>Door safety switch</i></li> </ul> | <ul style="list-style-type: none"> <li>● Termostato de seguridad <i>Safety thermostat</i></li> <li>● Lámpara interior <i>Halogen chamber light</i></li> <li>● Inversor de giro <i>Reversing gear</i></li> </ul> |
|---|---|

## OPCIONES (PVP) options (rrp)

- |                |                                     |              |
|----------------|-------------------------------------|--------------|
| ● GRILL 2,2 kW | ● HUMIFICADOR.<br><i>humidifier</i> | ● KIT GN 1/1 |
|----------------|-------------------------------------|--------------|

PVP rrp RX-604